

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/090737 A1

(51) International Patent Classification⁷: **E21B 1/26**

(74) Agent: LEE, Jea Ryang; 5F, Gwangju Small & Medium, Business Support Center 621-15, Dochen-dong, Gwangsan-Gu, Gwangju 506-301 (KR).

(21) International Application Number:
PCT/KR2005/000862

(22) International Filing Date: 24 March 2005 (24.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0020138 24 March 2004 (24.03.2004) KR
10-2004-0057657 23 July 2004 (23.07.2004) KR

(71) Applicant and


(72) Inventor: IN, Suk Shin [KR/KR]; jungheung S-CLASS APT. 101-1405, 976, Yongbong-dong, Buk-gu, Gwangju 500-670 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: WATER HAMMER



(57) Abstract: A water hammer using a drive rod is provided. The water hammer includes a tubular main body having a hollow portion; a socket coupled to an upper end of the main body and having a water pressure supply passage; a cylindrical piston housing connected to the main body; a piston slidably installed in the piston housing, for striking a bit of a bit unit installed at a lower portion of the main body, having a hollow portion through which water is discharged, an annular pressurizing portion protruding on its outer circumferential surface, and a first communication hole connected to the hollow portion; a sliding member fitted into the main body to be coupled to the piston housing, defining a valve installation space, and creating a space portion in which the piston is received when the piston is elevated; a valve member defining the valve installation space into first and third space portions along the length of the piston, the first and second space portions having different cross-sectional areas from each other, and valve member forming a second space portion between the first and third space portions, connected to the hollow portion of the piston and connected to the first space portion when the piston is elevated; and a water pressure supply unit for supplying high pressure water delivered to the water pressure supply passage of the socket to the first and second space portions.

WO 2005/090737 A1